



 48	 48		
Hydraulic	Trend / Reverse trend	Adjustable height	
 109	 68	 109	 68
Total length	Total width	Useful length	Useful width
	 10	 33	 135
Spring	Ø Wheels	Weight	Patient weight

## Characteristics

This patient hygiene stretcher is specially designed to help the minimum hygiene level, ergonomically, to those patients that has not balance sited or up righted.

Some of its main characteristics are:

- Structure:

Resistant chassis made on stainless steel tube with epoxy-polyester coating that protects it against corrosion, also makes it easy to maintain and clean. It is resistant to all types of dis-solvent.

- Base:

It is made of reinforced fibre, which increases the stretcher resistance, allowing a high working load.

- Mattress:

It has a removable mattress, anti-splatter and totally hermetic.

It is made of PES, granting high heat, water and vapour resistance. It is totally flat, seamless, soft and padded.

- Lifting:

Driven by a hydraulic actuator, for the height regulation activated by pedals.

Elevation range: 280 mm.

- Trendelenburg / Reverse trendelenburg:

It can be tilted to Trendelenburg position, by a gas spring driven by an easy to use lever. It allows a longitudinal tilt of 12° to facilitate the water evacuation.

- Side rails

High security high rails, with locking/releasing device to guaranty the patient weight support.

- Drainage:

Drainage tube connected to the mattress and made of its same material.

Drainage hole in the mattress. It includes a cap to avoid losing water whilst washing care is done.

- Other characteristics:

It has side channels and drainage hole that permits an easy dewatering of the mattress.

It has four (4) double wheels with Ø125 mm, the wheels on the back has total brake.



# PatientHygieneStretcher



## Información técnica

Total length (Exterior)	1900 mm.
Total width (Exterior)	720 mm.
Useful length	1730 mm.
Useful width	520/620 mm.
Maximum height	800 mm.
Minimum height	520 mm.
Trendelenburg tilting angle	12°
Wheels diameter	125 mm.
Drainage tube length	1000 mm
Stretcher weight	45 kg.
Maximum patient weight (MPW)	175 kg.

## Standard

### Controls



Hydraulic lifting



Hydraulic Trend

### Protection



Foldable rails

### Transport



Double  
Ø120mm




Independent  
brake

### Wellness



Padded  
mattress

### Others



Drainage tube



Drainage hole